



KONICA MINOLTA

bizhub 225i
Multifuncțional A3 alb-negru

**bizhub
i-SERIES IS
SMARTER
WORKING**

RETHINK IT



Giving Shape to Ideas

BENEFICIILE CLIEŢILOR



Servicii

Gestionarea eficientă a echipamentelor, inclusiv livrare automată de consumabile, mentenanță pro-activă și configurare de la distanță

OPȚIUNI

1 ALTELE

Alimentator documente
DF-633

Capac originale
OC-512

SALU

Unitate duplex
AD-509

4 IEȘIRE HÂRTIE

Capsator extern
EH-C591

2 CONECTIVITATE

Panou opțional
MK-750

Placă fax
FK-510

Wireless LAN
SX-BR-300AN

3 ALIMENTARE HÂRTIE

Tavă hârtie
PF-507

x4

Masă (mare)
DK-706

Masă (medie)
DK-707

SALU

Masă (mică)
DK-708

SALU



LEGENDĂ

- Opțiune obligatorie
- Opțiune
- Această opțiune se poate instala doar împreună cu opționalul de deasupra

FUNȚIONALITĂȚI DE FINISARE



Duplex



Capsare
în colț
(offline)

DESCRIPTION

CONNECTIVITY

FK-510 Fax board	Super G3 fax
SX-BR-300AN Wireless LAN	Wireless LAN to network connector
MK-750 Optional Panel	Needed for fax function and scan one-touch destinations

OTHERS

DF-633 Document feeder	Reversing automatic document feeder, capacity 130 originals
OC-512 Original Cover	Cover instead of ADF
AD-509 Duplex unit	For duplex printing and copying

MEDIA INPUT

PF-507 Paper Tray	250 sheets, B5-A3, 64-90 g/m ²
DK-706 Copier desk (large)	For no or 1x PF-507
DK-707 Copier desk (medium)	For 2x PF-507
DK-708 Copier desk (small)	For 3x or 4x PF-507

MEDIA OUTPUT

EH-C591 Convenience stapler	Convenient stapling of up to 50 sheets per set
-----------------------------	--

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

System speed A4	Up to 22 ppm
System speed A3	Up to 8 ppm
Autoduplex speed A4	Up to 15 ppm
1st page out time A4	6.5 sec.
Warm-up time	Approx. 15 sec. ¹
Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Panel size/resolution	5 line LCD / 128 x 64
System memory	256 MB (standard/max)
Interface	10/100-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n (optional)
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP
Automatic document feeder (optional)	Up to 130 originals; A5-A3; 35-128 g/m ² ; RADF
Printable paper size	A5-A3; customized paper sizes
Printable paper weight	64-157 g/m ²
Paper input capacity	350 sheets/1,350 sheets (standard/max)
Paper tray input (standard)	1x 250; A5-A3; custom sizes; 64-157 g/m ²
Paper tray input (optional)	1x 250 sheets; B5-A3; custom sizes; 64-90 g/m ² (up to 4x)
Manual bypass	100 sheets; A5-A3; custom sizes; 64-157 g/m ²
Finishing modes (optional)	Group; Sort; Staple (offline)
Automatic duplexing	A5-A3; 64-90 g/m ²
Output capacity	Up to 250 sheets
Duty cycle (monthly)	Rec. 5,000 pages; Max. ² 15,000 pages
Toner lifetime	Black up to 12,000 pages
Imaging unit lifetime	Black up to 55,000/55,000 pages (drum/developer)
Power consumption	220-240 V / 50/60 Hz; Less than 1.30 kW
System dimension (W x D x H)	607 x 570 x 458 mm (without options)
System weight	Approx. 28.2 kg (without options)

PRINTER SPECIFICATIONS

Print resolution	600 x 600 dpi
Page description language	GDI
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Linux

SCANNER SPECIFICATIONS

Scan speed	Up to 55/20 ipm in simplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail; Scan-to-SMB; Scan-to-FTP; Scan-to-USB; TWAIN scan
File formats	JPEG; TIFF; PDF
Scan destinations	32 destinations; 250 speed dials; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax
Fax resolution	Up to 406 x 392 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	32 destinations; 250 speed dials

SYSTEM FEATURES

Accounting	Up to 50 user accounts
Software	Net Care Device Manager; Web Connection

¹ Warm-up time may vary depending on the operating environment and usage

² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m² quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

Simitri HD
High Definition Polymerised Toner

Simitri
with Biomass

