

Maintain peak productivity with Canon's flagship mono laser printer.

i-SENSYS
LBP6780x

you can



Canon's flagship mono laser printer with MEAP integrates seamlessly into busy printing environments.

Canon's flagship mono A4 laser printer offers fast 40ppm output. Network ready, MEAP-enabled and with a robust design, it integrates seamlessly into busy offices and workgroups.

Key features

- 40ppm mono laser printer that's ideal for business workgroups
- Up to 1200 x 1200 dpi equivalent print resolution creates superb quality results
- No waiting with Quick First-Print technologies
- Productive First Print Out Time of just 8 seconds
- MEAP enabled for uniFLOW and solution integration
- Max. 1600-sheet paper capacity to keep downtime to a minimum
- Productive automatic double-sided printing
- Network ready
- PCL5e/6 and Adobe PostScript Level 3 support
- Direct print from USB storage
- Highly energy efficient
- Canon Mobile Printing app for iPad® and iPhone®

What's in the box

Main unit, 724 cartridge, power cord, starter guide and warranty card with user software and manual CDs.

Dimensions (W x D x H)

454mm x 424mm x 345mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 / (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit)

Mac OS 10.4.9 and up
(Web distribution only)

Linux (Web distribution only)

Citrix



Canon



- 1 5-line LCD display
- 2 100 sheet multi-purpose tray
- 3 500-sheet tray
- 4 x 2 Optional 500-sheet cassettes
- 5 Cartridge 724
- 6 Cartridge 724H

Specifications:

PRINTER ENGINE	Print speed: 40ppm mono (A4) Printing method: Monochrome laser beam printing Print quality: Up to 1200 x 1200 dpi Print resolution: Up to 600 x 600 dpi Warm-up time: 28 seconds or less First Page Out Time: 8.6 seconds Duty cycle: Max. 100,000 pages per month ¹ Print margins: 5mm top, bottom, left and right (envelope: 10mm)
MEDIA HANDLING	Paper input (Standard): 500-sheet cassette Paper input (Option): 100-sheet multi-purpose tray Paper output: 500-sheet cassette x 2 Media types: 250-sheet face down, 50-sheet face up Plain paper, Heavy paper, Transparency, Label, Index card, Envelope Media sizes: Cassette (Standard and optional): A4, B5, A5, A5 landscape, A6, LGL, LTR, Executive, 16K Custom sizes: Width: 105.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, A5 landscape, A6, LGL, LTR, Executive, 16K Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm Media weights: Cassette (Standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 199 g/m ²
GENERAL FEATURES	Power requirements: 220-240V (±10%) 50/60Hz (±2Hz) Power consumption: Maximum: Approx. 1,400 W or less Active: Approx. 660 W Standby: Approx. 15 W Sleep modes: Approx. 5.4 W (Sleep Mode 1) Approx. 1 W (Sleep Mode 2) Typical Electricity Consumption (TEC): 1.9 kWh/Week Noise level: Sound power ² : Active: 7.3 B or less Standby: Inaudible Sound pressure ² : Active: 54.5 dB(A) or less Standby: Inaudible Dimensions (W x D x H): 454mm x 424mm x 345mm Weight: Approx. 16.6kg Operating environment: Temperature: 10 to 30°C (50 to 86°F). Humidity: 20 to 80% RH (no condensation) Control panel: 5 line LCD display 9 LED indicators 12 Operation keys

CONTROLLER	Processor Speed: 528MHz + 264MHz Memory: 768 MB Printer languages: UFR II (Ultra Fast Rendering), PCL5e, PCL6, Adobe® PostScript Level 3 Fonts: 93 PCL fonts, 10 Bitmap fonts, 136 PS fonts Software and printer management: Remote User Interface (RUI), Secure Print with optional SD Card-B1, Canon Mobile Printing app for iPad® and iPhone® Interface and connectivity: USB Host, USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T Operating systems compatibility: Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 R2 (64bit) Mac OS 10.4.9 and up ³ / Linux ³ / Citrix
CONSUMABLES	All-in-One cartridges: Standard: Cartridge 724 (6,000 pages) ⁴ High yield: Cartridge 724H (12,500 pages) ⁴
ACCESSORIES / OPTIONS	Items: Paper Feeder PF-45 (500-sheet cassette) SD Card-B1 Barcode Printing Kit - F1 (Barcode ROM module)
Standard disclaimers. All specifications subject to change without notice. 1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product 2] Declared noise emission in accordance with ISO 9296 3] Web distribution only 4] Based on ISO/IEC 19752	

